AMENDMENT OF SOLICITATION/MODIFICATION OF CONTRACT					1. CONTRACT ID CODE		PAGE OF PAGES 1 3
0001 19 M		ECTIVE DATE May 2003	4. REQUISITION/PURCHASE REQ. NO. W38XGR-3076-1678		5. PROJECT NO. (If applicable) DACW66-03-B-0006		
6. ISSUED BY	CODE W382	XGR	7. ADMINISTERED BY (If a	other 1	than Item 6)	CODE	
Department of the Army Memphis District, Corps of Engi 167 North Main Street, Rm B202 Memphis, TN 38103-1894	neers 2 ATTN: CEMV	M-CT					
8. NAME AND ADDRESS OF CONTRACTOR (No., street, county, State and ZIP Code)					9A. AMENDMENT OF SOLICITATION NO. DACW66-03-B-0006		
				×	9B. DATED (SE 29 APR 20	,	
					10A. MODIFICA NO.	ATION OF CON	TRACTS/ORDER
					10B. DATED (S	SEE ITEM 13)	
CODE 1		TY CODE	AMENDMENTS OF SO	אוור	ITATIONS		
The above numbered solicitation is a tended.						tended, X i	s not ex-
Offers must acknowledge receipt of this a	amendment prior to th	e hour and date specif	ied in the solicitation or as a	men	ded, by one of th	ne following me	ethods:
(a) By completing Items 8 and 15, and resubmitted; or (c) By separate letter or teleMENT TO BE RECEIVED AT THE PLACE IN REJECTION OF YOUR OFFER. If by viriletter, provided each telegram or letter materials	egram which includes DESIGNATED FOR THE tue of this amendmen	a reference to the soli E RECEIPT OF OFFERS t you desire to change	PRIOR TO THE HOUR AND an offer already submitted,	nbers DAT such	s. FAILURE OF YO E SPECIFIED MA n change may be	OUR ACKNOW Y RESULT made by teleg	LEDG- ram or
12. ACCOUNTING AND APPROPRIATION	DATA (If required)						
			DIFICATIONS OF CON ER NO. AS DESCRIBE			6,	
A. THIS CHANGE ORDER IS ISSUE TRACT ORDER NO. IN ITEM 10/	D PURSUANT TO: (S _F A.	pecify authority) THE C	HANGES SET FORTH IN ITE	VI 14	ARE MADE IN T	HE CON-	
B. THE ABOVE NUMBERED CONTF appropriation date, etc.) SET FOR				ES ((such as changes in	paying office,	
C. THIS SUPPLEMENTAL AGREEME	NT IS ENTERED INTO	PURSUANT TO AUTH	HORITY OF:				
D. OTHER (Specify type of modification	and authority)						
E. IMPORTANT: Contractor	is not, i	s required to sign	this document and re	turn	co	pies to the	issuing office.
14. DESCRIPTION OF AMENDMENT/MOD	DIFICATION (Organized	l by UCF section heading	s, including solicitation/contrac	t subj	ject matter where fe	easible.)	
This solicitation for Trotters, Mis 2:30 p.m., is amended as follows	ssissippi Landside ::	Berm - Parcel 1,	Tunica County, Missi	ssip	pi, scheduled	to open 29	MAY 2003 at
1. DRAWING NO. 2. Drawing	No. 2, File No.	102/002b0311 is	deleted and replaced w	ith I	Drawing No.	2, File No.	102/002c0311.
2. Section 00100 - Instructions to entirety.	o Bidders: Contra	act Clause No. 52	.232-15 entitled "Prog	ress	Payments No	ot Included"	, is deleted in its
Except as provided herein, all terms and cand effect.	conditions of the docu	ment referenced in Ite	m 9A or 10A, as heretofore	chan	iged, remains und	changed and in	full force
15A. NAME AND TITLE OF SIGNER (Type	e or print)		16A. NAME AND TITLE OF	CON	NTRACTING OFFI	ICER (Type or p	print)
15B. CONTRACTOR/OFFEROR		15C. DATE SIGNED	16B. UNITED STATES OF A	AMEF	RICA		16C. DATE SIGNED
(Signature of person authorize	nd to cianl			2 of 1	Contracting Office	orl	

3. Specifications Section 02230, Paragraph 3.4.1. Delete paragraph 3.4.1 in its entirety and replace it with the following paragraph 3.4.1:

3.4.1 General

The borrow areas shall conform to requirements prescribed herein and as shown on the drawings. The permissible depth in the borrow pits is 8 feet below natural ground, but the right is reserved in accordance with the CONTRACT CLAUSE entitled "Changes" to modify the permissible depth in accordance with subsurface conditions determined as work proceeds and/or as directed by the Contracting Officer. Slopes on three sides of each borrow pit shall be constructed to 1V on 3H with slopes on the remaining side constructed to 1V on 10 H as shown on the plans. Pit boundaries shall be irregular, but contained within the right-of-way limits provided on the drawings. The borrow areas excavated under this contract shall be drained and kept dry during excavation, as excavation will not be permitted in water nor shall excavated material be scraped, dragged or otherwise moved through water. Drainage of the borrow areas during excavation shall be accomplished at the Contractor's expense by ditching, sump pumping or other approved methods. The borrow areas excavated under this contract and flooded during high water stages shall be drained and allowed to dry as quickly as practicable after the high water has passed. The rights-of-way for drainage during excavation shall be the rights-of-way shown on the drawings; however, the Contractor, at his option, may use the rights-of-way for drainage outside the rights-of-way shown on the drawings provided that their location and dimensions are approved by the Contracting Officer, and provided that the Contractor has submitted written evidence to the Contracting Officer that he has obtained the rights-of-way from the property owners. The written evidence shall consist of an authenticated copy of the conveyance under which the Contractor acquired the rights-of-way, prepared and executed in accordance with the laws of the State of Mississippi. If temporary rights are obtained by the Contractor, the period of time shall coincide with SECTION 0800, paragraph 1.1 hereof, plus a reasonable time for any extension granted for completion of the work. The Contractor shall be solely responsible for any and all damages, claims for damages, and liability of any nature whatsoever arising from or growing out of the use of rights-of-way for drainage outside of the rights-of-way indicated on the drawings. Except as required by variable right-ofway widths and the irregular pit boundaries as described above, abrupt changes in borrow area alignment shall be avoided. The excavation of the borrow areas shall be made throughout the length of the borrow areas, and be continuous at full depth as applicable to each pit as necessary to provide the required quantity of suitable available fill material and to meet the requirement of construction of an island in each pit as specified herein below. At least one island shall be constructed in each borrow pit. Each island will have an exposed crown width of 6 to 8 feet, a length of 20 feet, and 1V on 5H side slopes. The location of the island shall be designated by the Contracting Officer. The island shall either consist of unexcavated material or shall be constructed after excavation utilizing suitable material remaining in the pit. The order of excavation in the borrow areas shall be as shown on the drawings. Moisture content will not be considered in determining suitability of material, however, moisture control as specified in paragraph 3.4.3 may be required by the Contracting Officer.

4. Specifications Section 02230, Paragraph 3.4.2. Delete paragraph 3.4.2 in its entirety and replace it with the following paragraph 3.4.2:

3.4.2 Pit Location and Depth

The three borrow areas shall be located as indicated on the drawings. The allowable depth of each borrow area shall conform to the applicable slopes originating at the applicable control line and descending to the applicable depth of 8 feet below natural ground as directed by the Contracting Officer, thence progressing at such depth, and toeing out on the applicable ascending slope, all within the boundaries of each borrow pit as shown on the drawings. Side and end slopes of the excavation shall be as shown on the drawings, unless otherwise directed by the contracting officer. No material shall be obtained closer to the levee than indicated on the drawings.

5. Specifications Section 02230, Paragraph 3.4.4. Delete paragraph 3.4.4 in its entirety and replace it with the following paragraph 3.4.4:

3.4.4 Excavation Plan

The excavation shall begin at the line specified on the plans for each borrow pit, and shall progress in the direction indicated on the plans. The fill material from the borrow pits shall be placed in the fill areas as specified in the plans and paragraph 3.5.2. The Contractor shall submit an excavation plan for each pit for approval by the Contracting Officer and shall not begin excavation until the Contracting Officer's approval has been received. The Contractor shall submit a plan for each pit for making optimum use of available borrow, including the Contractor's proposed methods for constructing the island in each pit.

6. Specifications Section 02230, Paragraph 3.4.5.2 Delete paragraph 3.4.5.2 in its entirety and replace it with the following paragraph 3.4.5.2:

3.4.5.2 Unsuitable Materials

Materials which are classified as unsuitable as fill material are defined as masses of organic matter, sticks, branches, roots, and other debris. These materials are unsuitable as fill material and will be ordered wasted and shall be disposed of in portions of the borrow pits excavated under this contract. The materials shall be placed in piles under the direction of the Contracting Officer.